



SIGNS EXPLANATION

All the below mentioned signs can be found on packagings, labels and/or on the company's technical documentation

	Min-max permanent application temperature		Low acidity (EN 60754-2)		KOUVIDIS Multilayer Pipes Technology																		
	Voltage limit		Product is made of halogen free raw materials (EN 50642)		Product Conformity to all requirements of relative European Directives.																		
	Ingress protection against solid objects and water (EN 60529)		Product with up to 99,9% antimicrobial protection		The product and its production process are inspected and approved by VDE German institute																		
	Non flame propagating product		Longitudinal stripes of indelible color indicate the power of the protected cables Red (RAL 3020) = power Green (RAL 6037) = telecommunication		Certification body of Bureau Veritas																		
	Product that propagates flame		Antistatic Technology IAS (Patent Protected 1009970)	<div style="border: 1px solid black; padding: 10px;"> <p style="text-align: center;">APPLICATIONS FIELDS</p> <table border="0" style="width: 100%;"> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Exposed</td> <td>Concealed floor / ceiling</td> <td>Outdoor</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Concealed (underplaster)</td> <td>Underfloor in screed</td> <td>Buried underground</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Concealed (dry wall)</td> <td>Concrete</td> <td>Wood</td> </tr> </table> <p> Best choice acc. to the Manufacturer and the application needs</p> <p> Recommended acc. to the Manufacturer and the application needs</p> <p> Not Recommended acc. to the Manufacturer and the application needs</p> </div>					Exposed	Concealed floor / ceiling	Outdoor				Concealed (underplaster)	Underfloor in screed	Buried underground				Concealed (dry wall)	Concrete	Wood
Exposed	Concealed floor / ceiling	Outdoor																					
Concealed (underplaster)	Underfloor in screed	Buried underground																					
Concealed (dry wall)	Concrete	Wood																					
	Product with extra UV stability		Friction Reduction at the internal wall of conduits																				
	Product is not an attractive food to rodents		Antiscratch Technology ISR (Patent Protected 1010513)																				
	Low smoke during combustion (EN 61034-2)		Anti - electromagnetic technology (Patent Protected 1009975)																				
	Double wall conduits loaded on a truck (m)		Packing (m/bundle)																				
	Packing (pieces/box)		Nominal outer diameter (mm)																				
	Packing (m/bar)		Nominal inner diameter(mm)																				
	Packing (m/coil)																						