

Light type Plastic conduit systems (320Nt)


KOUVIDIS metal clamp for drywall



Properties

Raw material

Galvanized steel, type Sendzimir (by adding aluminum in the zinc texture), which provides maximum antioxidant protection



Application Standard

EN 61386.25



Type	Part number		
Ø16	6000024	108	432
Ø20	6000025	96	384
Ø25	6000026	72	288
Ø32	6000027	48	192

Mounting instructions: KOUVIDIS metal clamp is suggested to be installed with the use of a hammer with head 25x25mm



The NEW specially designed metallic clamp of KOUVIDIS

provides **fast, easy** and **safe mounting** for the new 3layer conduits SILCOR® PLUS - SIFLEX® PLUS and SUPERSOL® PLUS and SUPERFLEX® PLUS on drywalls and chipboards.

It is produced from galvanized steel, type Sendzimir (by adding aluminum in the zinc mixture), which provides maximum antioxidant protection, high mechanical strength and durability over time.

Mounting the metal clamp is very easy, avoiding piercing; it is installed with the single use of a hammer (suggested hammer head 25x25mm). Each side has three hooks out of which the two have a special bent and thus they do not traumatize the dry wall or the wooden wall while they are penetrated into the inner body. The middle hook is vertical, providing thus the necessary strength for the clip's safe installation.

Hooks' length is designed to not surpass the width of the dry wall or wooden wall. Finally, the special notches at the side walls of KOUVIDIS metal clamp hold the conduit evenly and protect it from the hammer's blow pressure.